



## Surface Scratches


Removal of surface scratches on a countertop finished with Bizzz™ Bees Wax



Tools and materials required to restore your Bizier countertop.



Bizzz™ Bees Wax



Sanding Block



Orbital Sander



Sand Paper. Steel Wool



Soft Cloth

Using the sanding block equipped with 150 grit sandpaper, sand the area to be restored in the direction of the wood grain until scratches disappear. If the scratches are still visible, use an orbital sander with 120 grit paper. After having removed the scratches, sand in the direction of the wood grain with 150 grit sandpaper on the sanding block. Wet the sanded part and let it dry. Lightly sand again with 180 grit sandpaper on the sanding block. As soon as the surface is smooth, stop sanding. Remove the wood dust with a vacuum cleaner. Apply a coat of Bizzz™ Bees Wax with a soft cloth and polish vigorously.

We recommend that you wait at least three months before restoring the surface of a new counter. The counter must adapt to your environment and your work habits. Remember that a countertop finished with Bizzz™ Bees Wax is very easy to restore, so do not be alarmed by a rough or stained surface.

**CAUTION:** Water or other liquids should not be left to stagnate (for example, overnight) under a rubber mat or cutting board. Rags or wet towels left to dry on the counter are also to be avoided. Sources of intense heat such as hot pans or small appliances that emit heat, should be kept away from solid wood countertops.

